

Diesel Fuel Tank Anti-Siphons

Pioneer HD Parts

2000 Fall River Ave., Seekonk, MA 02771
Phone: 508.336.7000 Fax: 508.336.5900



Specifications for Determining Anti Siphon Installs

Application	Part No.	ID	Length
Volvo, Mack, International w/ 3" Fill Neck	3-7	Ø 3.00"	7.0"
Volvo, Mack, International w/ 2.5" Fill Neck	25-675	Ø 2.50"	6.75"
Kenworth w/ 2.5" Fill Neck	25-95	Ø 2.50"	9.5"
Freightliner w/ 2.25" Fill Neck	225-95	Ø 2.25"	9.5"
Reefer & Medium-Duty International 1.875" Fill Neck (Fits 1 7/8")	187-75	Ø 1.875"	7.5"
2" Medium-Duty Fill Neck & M2 series Freightliner	2-7	Ø 2.0"	7.0"



3-7, 25-675, 25-95 & 225-95 are for Heavy-Duty Truck Diesel Fuel Tank Applications.

187-75 & 2-7 are for Medium-Duty Truck Diesel Fuel Tank Applications.

Measurements are from the Inside Diameter (ID) of the fuel tank neck.

Anti Siphons are guaranteed for the life of the fuel tank they are installed in. They do not restrict fueling and there is no splash-back. They cannot be broken out or taken out by fuel thieves. Patented and quality built in the USA. Over 450,000 in use! **Installs in less than 10 seconds!**

Freightliner Class 8 are 2 1/4" ID. Volvo, Mack, and International are either 2.5" or 3". **A measurement of the ID of the fuel tank necks is always advised.** Medium Duty Class 7 Mack & International are usually 1 7/8" ID, Freightliner are usually 2". Reefer tanks are 1 7/8". There are no Anti-Siphons made for 4" fuel tank necks. (Pre 1996 fuel tank necks are not guaranteed to be compatible to Anti-Siphons as sizes vary, always measure these models as many are 4").